



TACTILE

Caratteristiche tecniche / Technical Features / Caractéristiques Techniques / Technische Eigenschaften

 P0050	 	NORMA STANDARS NORME NORM	RISULTATO PROVA TEST RESULTS RESULTATS DES ESSAIS ERGEBNISSE
	Classificazione prodotto Product classification Classement Klassifizierung	UNI EN 14411 ISO 13006	Gruppo B1 UGL Completamente Greificato B1 UGL Group fully vitrified Group B1 UGL grès cérame fin Gruppe B1 UGL Feinsteinzeug
	Caratteristiche dimensionali e d'aspetto Dimensional and surface quality Caractéristiques de la surface Oberflächenqualität	UNI EN ISO 10545-2	Tolleranze minime Very low tolerance Des tolérances minimales Entspricht Normen
	Assorbimento di acqua Water absorption Absorption d'eau Wasseraufnahme	UNI EN ISO 10545-3	<=0,10%
	Resistenza alla flessione Flexural strength Résistance a la flexion Biegezug-Festigkeit	UNI EN ISO 10545-4	N/mm ² 50-60
	Resistenza al gelo Frost Resistance Résistance au gel Frostwiderstandsfähigkeit	Qualsiasi norma All standards Tout norme Jade beliebige Norm	Garantita Guaranteed Garantie Frostsicher
	Resistenza attacco chimico (esclusione acido fluoridrico) Resistance to acids and alkalis with the exception of hydrofluoric acid Résistance à l'attaque chimique (exclusion de l'acide fluorhydrique) Säure und Laugen Beständigkeit (mit Ausnahme von Fluorwasserstoff)	UNI EN ISO 10545-13	Nessuna alterazione No damage Non attaquées Nicht angegriffen
	Resistenza Usura e abrasione Wear and abrasion resistance Résistance à l'usure et abrasion Abreibhärte		Illimitata Adequate for all purposes Illimitée Unbegrenzt
	Dilatazione termica lineare Linear thermal expansion Coefficient linéaire e dilatation thermique Lieare Wärmeausdehnung	UNI EN ISO 10545-8	6x10 ⁻⁶
	Resistenza dei colori alla luce Light fastness Résistance de la couleur à la lumière Unveränderlichkeit der Farben wenn Strahlung zugesetzt wird	DIN 51094	Nessuna variazione No change of colours Couleurs inchangées Keinerlei Farbänderung